

# P10600V70C\_T31

7.0 Inches, 1024xRGBx600, 65K Colors, UnicView LCM



● Display

Item	Parameter	Description
Color	65K (65536) colors	16 bit color 5R6G5B
Visual Angle L/R/U/D	85° /85° /85° /85°	
Resolution	1024*600	90° rotated display (600*1024)
Backlight /Lifecycle/Brightness	LED/20,000 HOURS/ 280 cd/m <sup>2</sup>	
Working Temperature	-20~+70°C/-30~+80°C	

● Voltage & Current

Item	Conditions	Min	Typ	Max	Unit
Power Voltage	-	6	12	35	V
Operation Current	VIN = 12V, Backlight on	-	300	-	mA
	VIN = 12V, Backlight off	-	10	-	mA

Note: Short-circuit J25 to choose Power Input as 5V (4.5V~5.5V)

● Interface

Item	Conditions	Min	Typ	Max	Unit
Baudrate	Standard	1200	115200	892900	bps
Interface	TTL/CMOS				
Data Format	1 byte for initial, 8 bytes for data, invalid bytes for checksum, 1 byte for end				
Socket	SMD2.0-8P with lock catch				

Note: Short-circuit J17 to choose RS232

● Peripherals

No.	Parameter	Description	
1	Touch Screen	4-wire resistance touch screen: P10600V70C_T31	
		4-wire capacitive touch screen: P10600V70C_P31	
		No touch screen: P10600V70C_N31	
2	Buzzer	YES	
3	RTC	YES	
4	USB	YES. For downloading offline or user data copy.	External board needed for online debugging
5	USB Mini	YES. For online debugging.	
6	Audio Port	Support *.MP3 format. No time limit for single file. Theoretically 4096 files at maximum. Loudspeaker: 8 Ω 2W.	
7	Memory	128M(support *.jpg files, maximum 65536 files theoretically), extended to 1G at maximum.	



