

# P10768V80I\_T37

8.0 Inches, IPS 1024xRGBx768, 65K Colors, UNICView LCM



### ● Display

Item	Parameter	Description
Color	65K (65536) colors	16 bit color 5R6G5B
Visual Angle L/R/U/D	85° /85° /85° /85°	
Resolution	1024*768	90° rotated display (768*1024)
Backlight /Lifecycle/Brightness	LED/20,000 HOURS/ 800 cd/m <sup>2</sup>	
Working Temperature/ Storage Temperature	-20~+70°C/-30~+80°C	
Static ESD	±15KV	

### ● Voltage & Current

Item	Conditions	Min	Typ	Max	Unit
Power Voltage	-	6	12	40	V
Operation Current	VIN = 12V, Backlight on	-	550	-	mA
	VIN = 24V, Backlight on	-	280	-	mA
	VIN = 12V, Backlight off	-	160	-	mA

### ● Interface

Item	Conditions	Min	Typ	Max	Unit
Baudrate	Standard	1200	-	115200	bps
Interface	RS-232C				
Data Format	1 byte for initial, 8 bytes for data, invalid bytes for checksum, 1 byte for end				
Socket	SMD2.0-8P with lock catch				

### ● Peripherals

No.	Parameter	Description	
1	Touch Screen	4-wire resistance touch screen: P10768V80I_T37	
		4-wire capacitive touch screen: P10768V80I_P37	
		No touch screen: P10768V80I_N37	
2	Buzzer	YES	
3	RTC	YES	
4	USB	YES. For downloading offline or user data copy.	External board needed for online debugging
5	USB Mini	YES. For online debugging.	
6	Audio	Support *.MP3 files. Theoretically 4096 file at maximum. Speaker power: 4 Ω 2W or 8 Ω 2W.	
7	Keyboard	Support external row keyboard (8*8 maximum).	
8	Memory	128M(support *.jpg files, maximum 65536 files theoretically), extended to 1G at maximum.	



