

P80480V70I_T31

7.0 Inches, 800xRGBx480, 65K Colors, UNICView LCM



● Display

Item	Parameter	Description
Color	65K (65536) colors	16 bit color 5R6G5B
Visual Angle L/R/U/D	70° /70° /50° /70°	
Resolution	800*480	90° rotated display (480*800)
Backlight /Lifecycle/Brightness	LED/20,000 HOURS/ 400 cd/m ²	
Working Temperature/ Storage Temperature	-30~+85°C/-30~+85°C	
Static ESD	±14KV	

● Voltage & Current

Item	Conditions	Min	Typ	Max	Unit
Power Voltage	-	6	12	40	V
Operation Current	VIN = 12V, Backlight on	-	260	-	mA
	VIN = 24V, Backlight on	-	140	-	mA
	VIN = 12V, Backlight off	-	80	-	mA

● Interface



Item	Conditions	Min	Typ	Max	Unit
Baudrate	Standard	1200	-	115200	bps
Interface	RS-232C				
Data Format	1 byte for initial, 8 bytes for data, invalid bytes for checksum, 1 byte for end				
Socket	SMD2.0-8P with lock catch				

Note: Short-circuit J17 to choose RS232


● Peripherals

No.	Parameter	Description	
1	Touch Screen	4-wire resistance touch screen: P80480V70I_T31	
		4-wire capacitive touch screen: P80480V70I_P31	
		No touch screen: P80480V70I_N31	
2	Buzzer	YES	
3	RTC	YES	
4	USB	YES. For downloading offline or user data copy.	External board needed for online debugging
5	USB Mini	YES. For online debugging.	
6	Audio	Support *.MP3 files. Theoretically 4096 file at maximum. Speaker power: 4 Ω 2W or 8 Ω 2W.	
7	Keyboard	Support external row keyboard (8*8 maximum).	
8	Memory	128M(support *.jpg files, maximum 65536 files theoretically), extended to 1G at maximum.	





Pin Name	Pin Definition	Remarks
VIN	7,8	POWER INPUT
GND	1,2	GND
DIN	4	DIN
DOUT	5	DOUT
NC	3,6	Not Defined



Part No.	P80480V70I_T31			
Datasheet	A4	Drawn by	Proculus	Date
Proportion	1:1	Verified by		Date
Unit	mm	Confirmed by		Date

